



Team Meeting 2019 Santos

Regis Neuenschwander

Deputy Director Engineering Division Brazilian Synchrotron Light Laboratory (<u>www.lnls.br</u>)

regis.terenzi@lnls.br



Why am I here ?

12th International Particle Accelerator Conference Hoz do Iguaçu - Brazil Nay 23-28, 2021

IPAC2



Why are we here, in Santos ?

12th International Particle Accelerator Conference

PAC21


Santos – Brazil May 2021





Tapioca Dices with pepper sauce **Bistrô Calixto**





Argentinian Beef **@ Puerto de Palos**






Canole **@ Piccolo Café**









Let's be Sirius now !










































Brazilian Center for Research in Energy and Materials






Sirius Parameters and subsystems






Multiple Bend Achromat chain reaction diagram










Créditos: Racional Engenharia






Overview on magnet-girder assembly

Light Source	description	f ₁ (Hz)	TF _{s2M&G}
ESRF	3 motorized jacks, remote alignment, manual horizontal adjustment, unsufficient stiffness	10 (<mark>7</mark>)	1.3 (2.2)
Spring-8	6 support points, stiff alignment mechanism	19	1.9
AP.S	4 Wedge Jacks	9.5 (10.5)	1.5 (9)
Petra III	Similar to Diamond: Girder pedestals, 5 cam systems, beam based girder alignement		
SLS	Girder pedestals, 5 cam systems, beam based girder alignement	15.5	
Soleil	4-points support when operation, 3 Airloc jacks when alignement	46	1.0
Diamond	Girder pedestals, 5 cam systems, remote alignement	16.3	4.6
SSRF	3 support points, Wedge Jacks and ball bearing, + 3 assistant supports	23	1.3
Alba	Fixed, 6- point support + vertical fixation	28	
NSLS II	8-points support, fixed, manual alignment	30	1.4
TPS (proto)	6 cam systems + locking systems	30	
÷			

Courtesy L. Zhang – Workshop on Accelerator R&D for USR





Overview on magnet-girder assembly

Light Source	description	f ₁ (Hz)	TF _{s2M&G}
ESRF	3 motorized jacks, remote alignment, manual horizontal adjustment, unsufficient stiffness	10 (<mark>7</mark>)	1.3 (2.2)
Spring-8	6 support points, stiff alignment mechanism	19	1.9
APS	4 Wedge Jacks	9.5 (10.5)	1.5 (9)
Petra III	Similar to Diamond: Girder pedestals, 5 cam systems, beam based girder alignement		
SLS	Girder pedestals, 5 cam systems, beam based girder alignement	15.5	
Soleii	4-points support when operation, 3 Airloc jacks when alignement	40	1.0
Diamond	Girder pedestals, 5 cam systems, remote alignement	16.3	4.6
SSRF	3 support points, Wedge Jacks and ball bearing, + 3 assistant supports	23	1.3
Alba	Fixed, 6- point support + vertical fixation	28	
NSLS II	8-points support, fixed, manual alignment	30	1.4
TPS (proto)	6 cam systems + locking systems	30	

Courtesy L. Zhang – Workshop on Accelerator R&D for USR






Figure 7: First vertical modal shape of girder at 116 Hz, girder on concrete stands

Courtesy Markus Schloesser

Overview on magnet-girder assembly

Light Source	description	f ₁ (Hz)	TF _{s2M&G}
ESRF	3 motorized jacks, remote alignment, manual horizontal adjustment, unsufficient stiffness	10 (7)	1.3 (2.2)
Spring-8	6 support points, stiff alignment mechanism	19	1.9
APS	4 Wedge Jacks	9.5 (10.5)	1.5 (9)
Petra III	Similar to Diamond: Grder pedestals, 5 cam systems beam based girder alignement	116	
SLS	Girder pedestals, 5 cam systems, beam based girder alignement	15.5	
Soleil	4-points support when operation, 3 Airloc jacks when alignement	40	1.0
Diamond	Girder pedestals, 5 cam systems, remote alignement	16.3	4.6
SSRE	3 support points, Wedge Jacks and ball bearing, + 3 assistant supports	25	1.3
Alba	Fixed, 6- point support + vertical fixation	28	
NSLS II	8-points support, fixed, manual alignment	30	1.4
TPS (proto)	6 cam systems + locking systems	30	

Courtesy L. Zhang – Workshop on Accelerator R&D for USR




JPHE

10 micrometer flatness girder


100 MPa compressive strength concrete

5 GPa compressive strength resin

High rigidity levelling units




V 1st mode: 268 Hz





H 1st mode: 152 Hz





BPM buttons












Ø = 6 mm

Ø = 10 mm



BPM buttons



wakelosses calculated from electromagnetic (wakefield) simulations based on Alun Morgan and Guenther Rehm work and help



Collaborative environment

JACOW.org

ABDW	DIPAC	HB	IPAC	PCaPAC
APAC	ECRIS	HIAT	LINAC	RuPAC
BIW	EPAC	IBIC	MEDSI	SAP
COOL	ERL	ICALEPCS	NA-PAC	SRF
CYCLOTRONS	FEL	ICAP	PAC	



Collaborative environment



ABDW	DIPAC	HB	IPAC	PCaPAC
APAC	ECRIS	HIAT	LINAC	RuPAC
BIW	EPAC	IBIC	MEDSI	SAP
COOL	ERL	ICALEPCS	NA-PAC	SRF
CYCLOTRONS	FEL	ICAP	PAC	

Great job !



Great job !

Collaborative environment

Many thanks !

JACOW.org

ABDW	DIPAC	HB	IPAC	PCaPAC
APAC	ECRIS	HIAT	LINAC	RuPAC
BIW	EPAC	IBIC	MEDSI	SAP
COOL	ERL	ICALEPCS	NA-PAC	SRF
CYCLOTRONS	FEL	ICAP	PAC	

Welcome to Brazil, welcome to Santos ... and a very productive week !